

IN THE CLAIMS

Please amend claims 1, 9 and 14 as follows:

Claim 1 (Currently Amended): A respiratory measurement system, comprising:

a plastic cord having a portion that is configured to be placed across a chest of a person,
the plastic cord being substantially transparent to x-rays; and,

a sensor coupled to an end of the plastic cord, the end of the plastic cord being configured
to be disposed away from the chest of the person, the sensor generating a measurement signal
indicative of an amount of linear displacement of the plastic cord during respiration by the
person.

Claim 2 (Original): The respiratory measurement system of claim 1 further comprising a device
generating a visual indication of respiratory function of the person based on the signal.

Claim 3 (Original): The respiratory measurement system of claim 2 wherein respiratory function
comprises a lung volume level.

Claim 4 (Previously Presented): The respiratory measurement system of claim 1 wherein the
plastic cord comprises a polypropylene string.

Claim 5 (Previously Presented): The respiratory measurement system of claim 1 further
comprising a plastic tube configured to be placed across the chest of the person, the plastic cord
being disposed in the plastic tube.

Claim 6 (Original): The respiratory measurement system of claim 1 wherein the sensor
comprises a linear position encoder.

Claim 7 (Previously Presented): The respiratory measurement system of claim 1 further
comprising:

a tabletop having a securing device and a pulley coupled thereto, wherein a first portion
of the plastic cord extends between the securing device and the pulley, the securing device and

the pulley being positioned on the tabletop to allow the chest of the person to be disposed between the securing device and the pulley.

Claim 8 (Previously Presented): The respiratory measurement system of claim 7 wherein a second portion of the plastic cord extends from the pulley to the sensor.

Claim 9 (Currently Amended): A method for measuring respiratory motion of a person, comprising:

disposing a portion of a plastic cord across a chest of the person, wherein a sensor is coupled to an end of the plastic cord and is disposed away from the chest of the person, the plastic cord being substantially transparent to x-rays; and,

generating a measurement signal indicative of an amount of displacement of the plastic cord during respiration by the person utilizing a the sensor coupled to the end of the plastic cord.

Claim 10 (Previously Presented): The method of claim 9 further comprising disposing a plastic tube across the chest of the person, the plastic cord being disposed in the plastic tube.

Claim 11 (Previously Presented): The method of claim 9 wherein the plastic cord comprises a polypropylene string.

Claim 12 (Original): The method of claim 9 further comprising providing a visual indication of respiratory function of the person based on the signal.

Claim 13 (Original): The method of claim 12 wherein said respiratory function comprises a lung volume level.

Claim 14 (Currently Amended): A medical diagnostic system, comprising:

a tabletop;

an X-ray device disposed proximate the tabletop;

a plastic cord that has a portion is configured to be placed across a chest of a person lying on the tabletop, the plastic cord being substantially transparent to x-rays; and,

a sensor operatively coupled to an end of the plastic cord generating a measurement signal indicative of an amount of displacement of the plastic cord during respiration by the person, the end of the plastic cord and the sensor being configured to be disposed away from the chest of the person the sensor being outside a scanning area of the X-ray device.

Claim 15 (Original): The medical diagnostic system of claim 14 further comprising a device generating a visual indication of respiratory function of the person based on the signal.

Claim 16 (Original): The medical diagnostic system of claim 15 wherein said respiratory function comprises a lung volume level.

Claim 17 (Previously Presented): The medical diagnostic system of claim 14 wherein the plastic cord comprises a polypropylene string.

Claim 18 (Previously Presented): The medical diagnostic system of claim 14 further comprising a plastic tube configured to be placed across the chest of the person, the plastic cord being disposed in the plastic tube.

Claim 19 (Previously Presented): The medical diagnostic system of claim 14 wherein the sensor comprises a linear position encoder.

Claim 20 (Previously Presented): The medical diagnostic system of claim 14 further comprising a securing device and a pulley coupled to the tabletop, a first portion of the plastic cord extending between the securing device and the pulley, the securing device and the pulley being positioned on the tabletop to allow a chest of the person to be disposed between the securing device and the pulley.

Please add new claims 21 and 22.

Claim 21 (New): A respiratory measurement system, comprising:

a plastic cord that is configured to be placed across a chest of a person, the plastic cord being substantially transparent to x-rays;

a sensor coupled to the plastic cord generating a measurement signal indicative of an amount of displacement of the plastic cord during respiration by the person; and

a tabletop having a securing device and a pulley coupled thereto, wherein a first portion of the plastic cord extends between the securing device and the pulley, the securing device and the pulley being positioned on the tabletop to allow the chest of the person to be disposed between the securing device and the pulley.

Claim 22 (New): A medical diagnostic system, comprising:

a tabletop;

an X-ray device disposed proximate the tabletop;

a plastic cord that is configured to be placed across a chest of a person lying on the tabletop, the plastic cord being substantially transparent to x-rays;

a sensor operatively coupled to the plastic cord generating a measurement signal indicative of an amount of displacement of the plastic cord during respiration by the person, the sensor being outside a scanning area of the X-ray device; and

a securing device and a pulley coupled to the tabletop, a first portion of the plastic cord extending between the securing device and the pulley, the securing device and the pulley being positioned on the tabletop to allow the chest of the person to be disposed between the securing device and the pulley.